

1

2

3

4

5

6

Wiring information

PLUG 87654321
C5e
87654321
JACK 2
JACK 1

SCALE 2/1

PIN.8
PIN.1

B

B

Specification :

Material :

1. Plastic Housing : ABS, UL 94-HB, with optional color.
2. RJ45 Jack :
 - 2-1. Housing : PBT+Glass Fiber, UL 94V-0.
 - 2-2. Contact Bracket : PBT+Glass Fiber, UL 94V-0.
3. RJ45 Jack Contact :
- 3-1. Material : Phosphor Bronze with Nickel plated.
- 3-2. Finish : 50 micro-inch Gold plated on Plug contact area.
4. RJ45 Plug :
- 4-1. Housing : (JE P/N PR8850) PC, UL 94V-2, Transparent color.
- 4-2. Contact Terminal : Phosphor Bronze with 50 micro-inch Gold plated.
5. IDC :
- 5-1. Housing : PC+Glass Fiber, UL 94V-2.
- 5-2. Terminal : Phosphor Bronze with Tin plated.
6. Assembly Type : Normal Molded, white PVC.
7. Cable Type : (UTP)Foil Shielded Twisted Pair, 24 AWG Stranded Conductor.
8. Cable Chip : SPCC with Nickel Plated.
9. Screw : Steel with Nickel Plated.
10. PCB : FR4, UL 94V-0.

C

C

SCALE 1/2

Remark : AAFDA06011301XX
(1)(1) XX : Plastic Color
05=White, 13=Ivory

Performance :

- a. Insertion force : 20N max. (IEC 60603-7-4)
- b. Retention strength : 7.7 kg between Jack and Plug.
- c. Operating temperature : -10°C to 60°C. (ISO/IEC 11801, ANSI/TIA/EIA 568 B.2)
- d. Life(mating cycles) :
 - * Jack : 750 cycles min. (ISO/IEC 11801, IEC 60603-7-4)

D

D

GENERAL TOLERANCE OF DIMENSIONS	DRAWING	27.SEP.2010	QIQI
X.XXX ±0.005	CHECK	27.SEP.2010	JANE
X.XX ±0.05	APPROVAL	27.SEP.2010	JAIMY
X.X ±0.1			

		ITEM NO.:		CAT5 2138
		DES.:		CAT.5E MODULAR "Y" WIRING ADAPTOR
SCALE	1/2 (A4)	UNIT	mm	
		DATE	NAME	
		DRAWING NO.	AAFDA06011301XX	MYWA06-C5E-XX(SA2)
DRAWING CLASSIFICATION		S	SHEET	1 OF 1

1

2

3

4

5

6

10cm