



PINOUT:

CONN1	CONN2
1	46
2	11
3	9
4	28
5	1
6	26
8	15
9	12
10	10
11	27
12	2
13	25
GND	GND+47+48+51+52

电气测试条件:
 1. 电压:DC 300V
 2. 绝缘阻抗:5MΩ
 3. 导通阻抗:5Ω

模号	DY-009 DY-025
号	DY-1043

No.	Item	DESCRIPTION	Q'TY	UNIT
1	线材	单芯线13C+DA 墨绿色 φ8.0 30AWG (7/0.1BC+φ0.85PVC)*13C+D(7/0.1BC)+AL	1	pcs
2	插头	DB15M 蓝胶芯 前镍后锡	1	pcs
3	插头	CFH60M 黑胶芯 镀镍	1	pcs
4	虫累	4*48.5 墨绿色成型 (DE-1002)	4	pcs
5	丝	PE料白色 (DE-1018)	16	G
6	内	45P墨绿色PVC料 (DE1002)	68	G
7	模	L=120 黑色	1	pcs
8	外模	0.08*8~*14"PE袋 单条包装	1	pcs
9	扎	纸箱--常规纸箱L460MM*W300MM*H300MM RoHS		箱

A	INITIAL RELEASE			14/11/10
REV	DESCRIPTION OF CHANGE			DATE
TOLERANCE				
	INCHES	MM		
.X	.015	.030		
.XX	.010	.010		
.XXX	.005	.005		
DRAWN BY	TOMY CHANG	SCALE	NONE	REV
		UNIT	MM	A
CHECK BY		SHEET	1/1	CUSTOMER:
		DATE	14/11/10	DWG No.:VID1068
CUSTOMER P/N:		TITLE:CAB-X.21MT		
		P/N:		